

AQUARIUM HEATER



YAH-50



YAH-100



YAH-200



YAH-300



YAH-500



YAH-800



YAH-1000

Model	Voltage	Frequency	Power	Pump power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
YAH-50	AC220-240V	50Hz/60Hz	50W	2W	<30L	20-35°C	1.3m	140×70×30mm
YAH-100	AC220-240V	50Hz/60Hz	100W	2W	<50L	20-35°C	1.3m	140×70×30mm
YAH-200	AC220-240V	50Hz/60Hz	200W	2W	<90L	20-35°C	1.3m	140×70×30mm
YAH-300	AC220-240V	50Hz/60Hz	300W	2W	<200L	20-35°C	1.8m	265×86×45mm
YAH-500	AC220-240V	50Hz/60Hz	500W	2W	<300L	20-35°C	1.8m	265×86×45mm
YAH-800	AC220-240V	50Hz/60Hz	800W	2W	<500L	20-35°C	2.3m	265×86×45mm
YAH-1000	AC220-240V	50Hz/60Hz	1000W	2W	<600L	20-35°C	2.3m	265×86×45mm



AR-630/650



AR-680/6100

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
AR-630	AC110V/220V/240V	50Hz/60Hz	300W	100-300L	20-35°C	2.2m	275x80x32mm
AR-650	AC110V/220V/240V	50Hz/60Hz	500W	300-500L	20-35°C	2.2m	275x80x32mm
AR-680	AC110V/220V/240V	50Hz/60Hz	800W	500-700L	20-35°C	2.2m	310x80x32mm
AR-6100	AC110V/220V/240V	50Hz/60Hz	1000W	700-900L	20-35°C	2.2m	310x80x32mm

AQUARIUM HEATER



YBH-50



YBH-100



YBH-200



YBH-300



YBH-500



YBH-800



YBH-1000

Model	Voltage	Frequency	Power	Pump power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
YBH-50	AC110V/220V/240V	50Hz/60Hz	50W	2W	<30L	20-35°C	1.3m	140×70×30mm
YBH-100	AC110V/220V/240V	50Hz/60Hz	100W	2W	<50L	20-35°C	1.3m	140×70×30mm
YBH-200	AC110V/220V/240V	50Hz/60Hz	200W	2W	<90L	20-35°C	1.3m	140×70×30mm
YBH-300	AC110V/220V/240V	50Hz/60Hz	300W	2W	<200L	20-35°C	1.8m	265×86×45mm
YBH-500	AC110V/220V/240V	50Hz/60Hz	500W	2W	<300L	20-35°C	1.8m	265×86×45mm
YBH-800	AC110V/220V/240V	50Hz/60Hz	800W	2W	<500L	20-35°C	2.3m	265×86×45mm
YBH-1000	AC110V/220V/240V	50Hz/60Hz	1000W	2W	<600L	20-35°C	2.3m	265×86×45mm

AQUARIUM HEATER



YDH-50



YDH-100



YDH-150



YDH-200

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
YDH-50	220-240V	50Hz/60Hz	50W	<30L	20-35°C	1.3m	115×45×25mm
YDH-100	220-240V	50Hz/60Hz	100W	<50L	20-35°C	1.3m	115×45×25mm
YDH-150	220-240V	50Hz/60Hz	200W	<70L	20-35°C	1.3m	115×45×25mm
YDH-200	220-240V	50Hz/60Hz	300W	<90L	20-35°C	1.3m	115×45×25mm



AR-950-9100

INFRARED CARBON FIBER AQUARIUM HEATER

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
AR-950	AC110V/220V/240V	50Hz/60Hz	500W	300-500L	20-35°C	3.4m	280×80×30mm
AR-980	AC110V/220V/240V	50Hz/60Hz	800W	500-700L	20-35°C	3.4m	280×80×30mm
AR-9100	AC110V/220V/240V	50Hz/60Hz	1000W	700-900L	20-35°C	3.4m	280×80×30mm

AQUARIUM HEATER



YJB-50



YJB-100



YJB-200



YJB-300



YJB-500



YC-210



YC-220



YC-230



YC-250

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
YJB-50	AC110V/220V/240V	50Hz/60Hz	50W	30-40L	22°C-31°C	1.8m	φ40×180mm
YJB-100	AC110V/220V/240V	50Hz/60Hz	100W	40-60L	22°C-31°C	1.8m	φ40×220mm
YJB-200	AC110V/220V/240V	50Hz/60Hz	200W	60-150L	22°C-31°C	1.8m	φ40×260mm
YJB-300	AC110V/220V/240V	50Hz/60Hz	300W	150-300L	22°C-31°C	1.8m	φ40×300mm
YJB-500	AC110V/220V/240V	50Hz/60Hz	500W	300-500L	22°C-31°C	1.8m	φ40×340mm
YC-210	AC110V/220V/240V	50Hz/60Hz	100W	<50L	13-33°C	1.8m	260mm
YC-220	AC110V/220V/240V	50Hz/60Hz	200W	50-100L	13-33°C	1.8m	300mm
YC-230	AC110V/220V/240V	50Hz/60Hz	300W	100-250L	13-33°C	1.8m	340mm
YC-250	AC110V/220V/240V	50Hz/60Hz	500W	250-400L	13-33°C	1.8m	390mm



AQUARIUM HEATER



ULB-60



ULB-100



ULB-200



ULB-200J



ULB-300/500



ULB-300J/500J



ULB-800/1000



ULB-800J/1000J

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
ULB-60	AC220-240V	50Hz/60Hz	60W	<30L	20-34°C	1.9m	130×63×32mm
ULB-100	AC220-240V	50Hz/60Hz	100W	30-40L	20-34°C	1.9m	130×63×32mm
ULB-200/J	AC220-240V	50Hz/60Hz	200W	40-60L	20-34°C	1.9m	208×80×39mm
ULB-300/J	AC220-240V	50Hz/60Hz	300W	150-300L	20-34°C/14-34°C	1.9m	273×80×39mm
ULB-500/J	AC220-240V	50Hz/60Hz	500W	300-500L	20-34°C/14-34°C	1.9m	273×80×39mm
ULB-800/J	AC220-240V	50Hz/60Hz	800W	500-700L	20-34°C/14-34°C	1.9m	298×80×39mm
ULB-1000/J	AC220-240V	50Hz/60Hz	1000W	700-900L	20-34°C/14-34°C	1.9m	298×80×39mm

Note: J type without temp display.



ARF-050



ARF-100



ARF-200



ARF-300

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
ARF-050	AC110V/220V/240V	50Hz/60Hz	50W	30-40L	20-35°C	1.2m	210×47×25mm
ARF-100	AC110V/220V/240V	50Hz/60Hz	100W	40-60L	20-35°C	1.2m	210×47×25mm
ARF-200	AC110V/220V/240V	50Hz/60Hz	200W	60-150L	20-35°C	1.2m	210×47×25mm
ARF-300	AC110V/220V/240V	50Hz/60Hz	300W	150-300L	20-35°C	1.2m	210×47×25mm



YH-50



YH-100



YH-200



YH-300



YH-500



YH-800

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
YH-50	AC220-240V	50Hz/60Hz	50W	<30L	20-35°C	1.3m	φ80×28mm
YH-100	AC220-240V	50Hz/60Hz	100W	<50L	20-35°C	1.3m	φ90×28mm
YH-200	AC220-240V	50Hz/60Hz	200W	<90L	20-35°C	1.3m	φ100×28mm
YH-300	AC220-240V	50Hz/60Hz	300W	<200L	20-35°C	1.8m	φ110×33mm
YH-500	AC220-240V	50Hz/60Hz	500W	<300L	20-35°C	1.8m	φ129×36mm
YH-800	AC220-240V	50Hz/60Hz	800W	<500L	20-35°C	2.3m	φ143×36mm

AQUARIUM HEATER



UC-060



UC-100



UC-200



UC-400



UC-600



UC-1000



URB-060



URB-100



UC-200J



UC-400J



UC-600J



UC-1000J

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
UC-060	220-240V	50Hz/60Hz	60W	<40L	20-34°C	1.9m	110×50×25mm
UC-100	220-240V	50Hz/60Hz	100W	<70L	20-34°C	1.9m	110×50×25mm
UC-200/200J	220-240V	50Hz/60Hz	200W	50-150L	20-34°C	1.9m	200×90×40mm
UC-400/400J	220-240V	50Hz/60Hz	400W	150-300L	20-34°C	1.9m	240×90×40mm
UC-600/600J	220-240V	50Hz/60Hz	600W	300-500L	20-34°C	1.9m	265×90×40mm
UC-1000/1000J	220-240V	50Hz/60Hz	1000W	700-900L	20-34°C	1.9m	290×90×40mm
URB-060	220-240V	50Hz/60Hz	60W	<40L	20-34°C	1.9m	110×60×35mm
URB-100	220-240V	50Hz/60Hz	100W	<70L	20-34°C	1.9m	110×60×35mm

Note: J type without temp display.

AQUARIUM GLASS HEATER



JRB-210



JRB-220



JRB-230



JRB-250

Model	Voltage	Frequency	Power	For tank capacity	Cable length	Temperature Range	Dimensions(LxWxH)
JRB-210	AC110V/220V/240V	50Hz/60Hz	100W	<50L	1.8m	13-33°C	260mm
JRB-220	AC110V/220V/240V	50Hz/60Hz	200W	50-100L	1.8m	13-33°C	300mm
JRB-230	AC110V/220V/240V	50Hz/60Hz	300W	100-250L	1.8m	13-33°C	340mm
JRB-250	AC110V/220V/240V	50Hz/60Hz	500W	250-400L	1.8m	13-33°C	390mm

AQUARIUM GLASS HEATER



AK-01S



AK-02



AK-03



AK-21



AK-22



AK-23



AK-32



AK-50

Model	Size	Fit for thickness glass	Feeding mode	Feeding mode	Power supply
AK-01S	125×80×120mm	1-17mm	12/24 Hours	50g/100g	5#battery×2
AK-02	125×80×120mm	1-17mm	8/12/24 Hours	50g/100g	5#battery/5V1A
AK-03(WIFI)	125×80×120mm	1-17mm	8/12/24 Hours/WIFI	50g/100g	5#battery/5V1A
AK-21	140×90×130mm	1-17mm	12/24 Hours	100g	5#battery×2
AK-22	140×90×130mm	1-17mm	8/12/24 Hours	100g	5#battery/5V1A
AK-23(WIFI)	140×90×130mm	1-17mm	8/12/24 Hours/WIFI	100g	5#battery/5V1A
AK-32	130×47×90mm	1-15mm	12/24/48 Hours	50g	Lithium Battery1200mAH/DC5V
AK-50	162×65×80mm	1-17mm	12/24/48 Hours	70g	Lithium Battery/DC5V



ELECTRONIC TEMPERATURE CONTROL HEATER



XRB-600



XRB-1000

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
XRB-600	AC110V/220V/240V	50Hz/60Hz	600W	300-500L	20-35°C	2m	320×75×34mm
XRB-1000	AC110V/220V/240V	50Hz/60Hz	1000W	700-900L	20-35°C	2m	370×75×34mm



EXTERNAL HEATER



EH-300



EH-500

Model	Voltage	Frequency	Power	Capacity	Hose adapter	Temperature Range	Cable length	Length
EH-300	110V/220V/240V	50Hz/60Hz	300W	80-120cm	12/16/20mm	20-35°C	1.5m	310mm
EH-500	110V/220V/240V	50Hz/60Hz	500W	100-150cm	12/16/20mm	20-35°C	1.5m	310mm



FREQUENCY CONVERSION HEATER



ARK-50



ARK-100



ARK-300



ARK-500



ARK-800



ARK-1000



ARK-50J



ARK-100J



ARK-300J



ARK-500J



ARK-800J



ARK-1000J

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
ARK-50/J	AC220-240V	50Hz/60Hz	50W	30-40L	20-35°C	1.8m	205×65×31mm
ARK-100/J	AC220-240V	50Hz/60Hz	100W	40-60L	20-35°C	1.8m	205×65×31mm
ARK-300/J	AC220-240V	50Hz/60Hz	300W	150-300L	20-35°C	1.8m	205×65×31mm
ARK-500/J	AC220-240V	50Hz/60Hz	500W	300-500L	20-35°C	2.2m	280×80×36mm
ARK-800/J	AC220-240V	50Hz/60Hz	800W	500-700L	20-35°C	2.2m	280×80×36mm
ARK-1000/J	AC220-240V	50Hz/60Hz	1000W	700-900L	20-35°C	2.2m	280×80×36mm

Note: J type without temp display.

FREQUENCY CONVERSION HEATING ROD



AH-300



AH-500



AH-800



AH-1000

Model	Voltage	Frequency	Power	Pump power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
AH-300	AC220-240V	50Hz/60Hz	300W	2W	<200L	20-35°C	1.8m	340×85×50mm
AH-500	AC220-240V	50Hz/60Hz	500W	2W	<300L	20-35°C	1.8m	340×85×50mm
AH-800	AC220-240V	50Hz/60Hz	800W	2W	<500L	20-35°C	2.3m	340×85×50mm
AH-1000	AC220-240V	50Hz/60Hz	1000W	2W	<600L	20-35°C	2.3m	340×85×50mm



BH-50



BH-100



BH-200



BH-300



BH-500



BH-800



BH-1000

Model	Voltage	Frequency	Power	Pump power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
BH-50	AC220-240V	50Hz/60Hz	50W	/	<30L	20-35°C	1.3m	140×65×25mm
BH-100	AC220-240V	50Hz/60Hz	100W	/	<50L	20-35°C	1.3m	140×65×25mm
BH-200	AC220-240V	50Hz/60Hz	200W	/	<90L	20-35°C	1.3m	140×65×25mm
BH-300	AC220-240V	50Hz/60Hz	300W	2W	<200L	20-35°C	1.8m	265×85×50mm
BH-500	AC220-240V	50Hz/60Hz	500W	2W	<300L	20-35°C	1.8m	265×85×50mm
BH-800	AC220-240V	50Hz/60Hz	800W	2W	<500L	20-35°C	2.3m	265×85×50mm
BH-1000	AC220-240V	50Hz/60Hz	1000W	2W	<600L	20-35°C	2.3m	265×85×50mm



YCB-50



YCB-100



YCB-200



YCB-300



YCB-500

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
YCB-50	AC220-240V	50Hz/60Hz	50W	30-40L	20-35°C	1.3m	210×36×34mm
YCB-100	AC220-240V	50Hz/60Hz	100W	40-60L	20-35°C	1.3m	210×36×34mm
YCB-200	AC220-240V	50Hz/60Hz	200W	60-150L	20-35°C	1.8m	250×36×34mm
YCB-300	AC220-240V	50Hz/60Hz	300W	150-300L	20-35°C	1.8m	275×36×34mm
YCB-500	AC220-240V	50Hz/60Hz	500W	300-500L	20-35°C	1.8m	300×36×34mm



INFRARED CARBON FIBER AQUARIUM HEATER



AQR-500



AQR-800



AQR-1000



AQR-1200

Model	Voltage	Frequency	Power	For tank capacity	Temperature Range	Cable length	Dimensions(LxWxH)
ARQ-500	AC220-240V	50Hz/60Hz	500W	300-500L	20-35°C	2.2m	150×175×30mm
ARQ-800	AC220-240V	50Hz/60Hz	800W	500-700L	20-35°C	2.2m	150×175×30mm
ARQ-1000	AC220-240V	50Hz/60Hz	1000W	700-900L	20-35°C	2.2m	150×175×30mm
ARQ-1200	AC220-240V	50Hz/60Hz	1200W	900-1000L	20-35°C	2.2m	150×175×30mm



INTELLIGENT HEATER



YL-060



YL-100



YL-200



YL-400



YL-600



YL-1000

Model	Voltage	Frequency	Power	For tank capacity	Temperature range	Cable length	Dimensions(LxWxH)
YL-060	AC110V/220V/240V	50Hz/60Hz	60W	<40L	20-34°C	1.9m	110×50×25mm
YL-100	AC110V/220V/240V	50Hz/60Hz	100W	<70L	20-34°C	1.9m	110×50×25mm
YL-200/200J	AC110V/220V/240V	50Hz/60Hz	200W	50-150L	20-34°C	1.9m	200×90×40mm
YL-400/400J	AC110V/220V/240V	50Hz/60Hz	400W	150-300L	20-34°C	1.9m	240×90×40mm
YL-600/600J	AC110V/220V/240V	50Hz/60Hz	600W	300-500L	20-34°C	1.9m	265×90×40mm
YL-1000/1000J	AC110V/220V/240V	50Hz/60Hz	1000W	700-900L	20-34°C	1.9m	290×90×40mm

Note: J type without temp display

