



| Model | Voltage | Frequency | Power | Output | Cable length | Weight | Dimensions(LxWxH) |
|---------|----------------|-----------|-------|----------|--------------|--------|-------------------|
| JVP-130 | 110V/220V/240V | 50Hz/60Hz | 6W | 4000L/h | 2.5m | 0.35kg | 66×61×114mm |
| JVP-131 | 110V/220V/240V | 50Hz/60Hz | 8W | 6000L/h | 2.5m | 0.4kg | 77×70×126mm |
| JVP-132 | 110V/220V/240V | 50Hz/60Hz | 12W | 8000L/h | 2.5m | 0.55kg | 87×80×135mm |
| JVP-133 | 110V/220V/240V | 50Hz/60Hz | 16W | 10000L/h | 2.5m | 0.65kg | 98×91×144mm |
| JVP-230 | 110V/220V/240V | 50Hz/60Hz | 8W | 6000L/h | 2.5m | 0.6kg | 118×61×122mm |
| JVP-231 | 110V/220V/240V | 50Hz/60Hz | 12W | 8000L/h | 2.5m | 0.65kg | 128×69×132mm |
| JVP-232 | 110V/220V/240V | 50Hz/60Hz | 26W | 15000L/h | 2.5m | 1.0kg | 162×80×150mm |



| Model | Voltage | Frequency | Power | Output | Cable length | Weight | Dimensions(LxWxH) |
|----------|----------------|-----------|-------|----------|--------------|--------|-------------------|
| XVA-600 | 110V/220V/240V | 50Hz/60Hz | 8W | 6000L/h | 2.5m | 0.45kg | 70×100×120mm |
| XVA-800 | 110V/220V/240V | 50Hz/60Hz | 22W | 8000L/h | 2.5m | 0.6kg | 78×105×140mm |
| XVA-1000 | 110V/220V/240V | 50Hz/60Hz | 45W | 10000L/h | 2.5m | 0.9kg | 88×115×160mm |



| Model | Voltage | Frequency | Power | Output | Cable length | Weight | Dimensions(LxWxH) |
|------------|----------------|-----------|-------|----------|--------------|--------|-------------------|
| JVP-100A/B | 110V/220V/240V | 50Hz/60Hz | 3W | 2500L/h | 2.5m | 0.4kg | 70×70×90mm |
| JVP-101A/B | 110V/220V/240V | 50Hz/60Hz | 6W | 3000L/h | 2.5m | 0.5kg | 77×77×101mm |
| JVP-102A/B | 110V/220V/240V | 50Hz/60Hz | 12W | 5000L/h | 2.5m | 0.5kg | 83×83×106mm |
| JVP-110 | 110V/220V/240V | 50Hz/60Hz | 3W | 2000L/h | 1.5m | 0.2kg | 40×58×70mm |
| JVP-120 | 110V/220V/240V | 50Hz/60Hz | 6W | 3000L/h | 2.5m | 0.3kg | 48×65×80mm |
| JVP-200A/B | 110V/220V/240V | 50Hz/60Hz | 6W | 5000L/h | 2.5m | 0.5kg | 115×65×75mm |
| JVP-201A/B | 110V/220V/240V | 50Hz/60Hz | 12W | 6000L/h | 2.5m | 0.5kg | 123×70×85mm |
| JVP-202A/B | 110V/220V/240V | 50Hz/60Hz | 24W | 12000L/h | 2.5m | 0.8kg | 158×80×100mm |
| JVP-402A/B | 110V/220V/240V | 50Hz/60Hz | 48W | 24000L/h | 3m | 1.6kg | 320×83×100mm |

Note: A type with sucker, B type with magnet.

Features

- Featuring a novel and elegant design, the wave-making direction is adjustable.
- Equipped with a flow regulator, the flow rate can be adjusted as desired.
- High flow rate for powerful wave-making, energy-efficient and quiet operation.



YVP-01A YVP-01B YVP-02A YVP-02B YVP-03A YVP-03B YVP-04A YVP-04B

| Model | Voltage | Frequency | Power | Output | Cable length | Weight | Dimensions(LxWxH) |
|-----------|----------------|-----------|-------|---------|--------------|---------------|-------------------|
| YVP-01A/B | 110V/220V/240V | 50Hz/60Hz | 3W | 1800L/h | 1.5m | 0.17kg/0.25kg | 56×50×130mm |
| YVP-02A/B | 110V/220V/240V | 50Hz/60Hz | 5W | 3000L/h | 1.5m | 0.22kg/0.3kg | 61×56×136mm |
| YVP-03A/B | 110V/220V/240V | 50Hz/60Hz | 7W | 4000L/h | 2.5m | 0.32kg/0.4kg | 69×65×148mm |
| YVP-04A/B | 110V/220V/240V | 50Hz/60Hz | 13W | 8000L/h | 2.5m | 0.42kg/0.5kg | 82×72×157mm |

Note: A type with sucker, B type with magnet.



YVP-21A YVP-21B YVP-22A YVP-22B YVP-23A YVP-23B

| Model | Voltage | Frequency | Power | Output | Cable length | Weight | Dimensions(LxWxH) |
|-----------|----------------|-----------|-------|----------|--------------|--------------|-------------------|
| YVP-21A/B | 110V/220V/240V | 50Hz/60Hz | 6W | 5000L/h | 2.5m | 0.43kg/0.5kg | 100×50×145mm |
| YVP-22A/B | 110V/220V/240V | 50Hz/60Hz | 12W | 6000L/h | 2.5m | 0.62kg/0.7kg | 117×57×150mm |
| YVP-23A/B | 110V/220V/240V | 50Hz/60Hz | 24W | 12000L/h | 2.5m | 0.9kg/1kg | 145×71×188mm |

Note: A type with sucker, B type with magnet.



CW-110 CW-110S CW-120 CW-120S CW-140 CW-140S CW-160

| Model | Input voltage | Input voltage | Power | Output | Suitable aquarium size | Weight | Dimensions LxWxH |
|---------|-------------------------|---------------|-------|---------------|------------------------|--------|------------------|
| CW-110 | AC100-240V 50Hz/60Hz | DC 24V | 10W | 500~4000L/h | 50~70cm | 0.7kg | 100×58×58mm |
| CW-110S | AC100-240V 50Hz/60Hz | DC 24V | 10W | 4000L/h | 50~70cm | 0.6kg | 100×58×58mm |
| CW-120 | AC100-240V 50Hz/60Hz | DC 24V | 20W | 700~8000L/h | 70~120cm | 0.9kg | 120×70×70mm |
| CW-120S | AC100-240V 50Hz/60Hz | DC 24V | 20W | 8000L/h | 70~120cm | 0.8kg | 120×70×70mm |
| CW-140 | AC100-240V 50Hz/60Hz | DC 24V | 40W | 1200~15000L/h | 100~150cm | 1.5kg | 132×80×80mm |
| CW-140S | AC100-240V 50Hz/60Hz | DC 24V | 40W | 15000L/h | 100~150cm | 1.1kg | 132×80×80mm |
| CW-160 | AC100-240V 50Hz/60Hz | DC 24V | 60W | 1700~20000L/h | 150~200cm | 1.8kg | 136×90×90mm |

Note: S series without controller.

TM

Features

- The unique control system with multiple wave-making modes can basically meet user needs.
- It adopts low-voltage 24V DC variable frequency technology, ensuring safety and energy efficiency.
- Sine wave technology results in less current inversion vibration and lower noise.
- It features functions such as stall protection, dry run protection, fault alarm, automatic restart, and one-key lock.



| Model | Voltage | Power | Output | Cable length | Weight | Dimensions(LxWxH) |
|--------|---------|-------|----------|--------------|--------|-------------------|
| YVS-25 | DC 24V | 25W | 12000L/h | 2.5m | 1kg | 65×65×140mm |